

DS-2CE76U0T-ITPF 4K Indoor Fixed Turret Camera



- 8 MP turret camera
- EXIR 2.0: advanced infrared technology with 30 m IR distance
- 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS).

▪ Specification

Camera	
Image Sensor	8.29 MP CMOS
Signal System	PAL/NTSC
Frame Rate	TVI: 8MP@12.5fps, 8MP@15fps, 4MP@25fps, 4MP@30fps, 2MP@25fps, 2MP@30fps AHD: 8MP@15fps CVI: 8MP@12.5fps, 8MP@15fps CVBS: PAL/NTSC
Resolution	3840 (H) × 2160 (V)
Min. illumination	0.01 Lux@(F1.6, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/12.5 s to 1/50,000 s NTSC: 1/15 s to 1/50,000 s
Lens	2.8 mm, 3.6 mm, 6 mm fixed lens
Horizontal Field of View	102.9° (2.8 mm), 79° (3.6 mm), 44.7° (6 mm)
Lens Mount	M12
Day & Night	ICR
WDR (Wide Dynamic Range)	Digital WDR
Angle Adjustment	Pan: 0 to 360°, Tilt: 0 to 75°, Rotation 0 to 360°
Menu	
Image Mode	STD/HIGH-SAT
AGC	Support
Day/Night Mode	Auto/Color/BW (Black and White)
White Balance	ATW/MANUAL
HLC	Yes
BLC (Backlight Compensation)	Yes
Language	English
Functions	Brightness, Sharpness, Mirror, Smart IR
Interface	
Video Output	TVI/AHD/CVI/CVBS
General	
Operating Condition	-40 °C to 50 °C (-40 °F to 122 °F), humidity: 90% or less (non-condensation)
Power Supply	12 VDC ±25%
Power Consumption	Max. 2.2 W
Material	Plastic
IR Range	Up to 30 m
Communication	HIKVISION-C
Dimensions	Φ 84.6 mm × 78.9 mm (Φ 3.33" × 3.11")
Weight	Approx. 150 g (0.33 lb.)

▪ Available Model

DS-2CE76U0T-ITPF(2.8mm)

DS-2CE76U0T-ITPF(3.6mm)

DS-2CE76U0T-ITPF(6mm)

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.

